

BANKS BBQ

COMBINE DEMOLITION DERBY

COMBINE REGULATIONS

- 1 PICKUP REEL OR BAT REEL REMOVED.
- 2 CUTTING BAR REMOVED.
- 3 CROP DIVIDERS REMOVED.
- 4 GLASS REMOVED FROM CABS.
- 5 INSTALL SEAT BELTS.
- 6 CRASH HELMETS REQUIRED.
- 7 ORIGINAL FUEL TANK REMOVED (5 GAL. LIMIT INSTALL IN GRAIN TANK).
- 8 RUBBER TIRES ONLY, NO FLUID OR FOAM IN TIRES.
- 9 STRAW CHOPPERS REMOVED.
- 10 HEADER HEIGHT 16-18 INCHES (FIXED SOLID).
- 11 UNLOADING AUGER WITHIN 10 INCHES.
- 12 RUB BARS CAN BE PLACED AROUND RADIATOR FOR PROTECTION.
- 13 PROTECTION AROUND VARIABLE SPEED ACCEPTABLE.
- 14 ALL CHAINS AND BELTS REMOVED THAT ARE NOT USED FOR FORWARD AND REVERSE MOTION.
- 15 DISABLED FLAG MOUNTED 3 FEET ABOVE GRAIN TANK.
- 16 FOR SAFETY ANY NUMBER OF IRON PIECES CAN BE USED.
- 17 REAR AXLE CANNOT BE NARROWED LESS THAN STRAW WALKERS UNLESS FACTORY OPTION.
- 18 ALL COMBINES NEED TO BE INSPECTED AND APPROVED BEFORE ENTRY BY JUDGES.
- 19 HILLSIDE COMBINES MUST BE FIXED SOLID.
- 20 COMBINES ARE ONLY INTENDED TO LAST A 15 MINUTE HEAT. OVER REINFORCEMENT WILL ONLY DELAY AND LENGTHEN THE ACTION, WHICH WILL ONLY LOSE THE AUDIENCE'S INTEREST. REINFORCEMENT IS SUBJECT TO JUDGES DECISION, CALL AND ASK IF IN DOUBT.
- 21 DRIVERS AREA MUST HAVE SUFFICIENT PROTECTION WITHOUT LIMITING DRIVERS VISIBILITY.
- 22 DRIVER PROTECTION: AN APPROVED CRASH HELMET, 2000 SNELL SPEC OR NEWER WITH CHIN STRAP IS REQUIRED. EYE PROTECTION IN THE FORM OF GOGGLES OR SAFETY GLASSES IS REQUIRED FOR ANY HELMET NOT HAVING A FULLY FUNCTIONAL FACE SHEILD. A FIRE RETARDANT SUIT IS HIGHLY RECOMMENDED, AT A MINIMUM LONG PANTS AND LONG SLEEVE SHIRT SHOULD BE WORN. STURDY BOOTS ARE RECOMMENDED OVER TENNIS SHOES OR SNEAKERS TYPE OF FOOT WEAR TO PROVIDE FOOT AND ANKLE PROTECTION.